



TECHNICAL DATA SHEET

BLOK-LOK™ With Graffiti Control

**READY TO USE SILANE/SILOXANE
with MICRO-LOK™
PENETRATING GRAFFITI AND WATER REPELLENT**

PRODUCT DESCRIPTION

Rainguard BLOK-LOK with Graffiti Control is a water-based, silane/siloxane graffiti & water repellent that combines high-quality penetrating chemical solids with an acrylic surface treatment component, to create a clear, deep-penetrating, and non-film-forming chemically-reactive masonry water repellent that contains no silicone oils, paraffin wax, or urethanes.

MICRO-LOK creates a micro-molecular chemical and mechanical bond between the water-repellent chemicals and the substrate. BLOK-LOK penetrates deep into porous masonry surfaces to provide long-lasting and virtually indestructible water-repellent protection that is not affected by weather or sunlight. The acrylic surface component make graffiti easy to remove with Rainguard's VandIClean Super or Graffiti Removal Spray.

BLOK-LOK provides superior grade, heavy-duty graffiti and water-repellent performance on a wide variety of vertical surfaces. This material comes in **Ready To Use and Concentrate formulas.**

PRODUCT FEATURES

- Exclusive MICRO-LOK formulation
- Mold and Mildew Inhibitor
- Protection not effected by weathering or UV light
- Single product provide protection against water and graffiti
- V.O.C. compliant
- Contains no known carcinogens
- Does not darken surfaces
- Breathable – does not trap moisture

Warranty Period:

Water Repellency—10 years
Graffiti Protection— 2 years

CSI Reference: Division 3, 4, 7 & 9

Part Numbers:	<u>USA</u>	<u>International</u>
1 Gallon RTU	CR-0609	CR-0609-CA
5 Gallon RTU	CR-0610	CR-0610-CA
55 Gallon RTU	CR-0611	CR-0611-CA
32oz Concentrate	CR-0612	CR-0612-CA
1 Gal Concentrate	CR-0614	CR-0614-CA

RECOMMENDED USES:

- Bare wood
- Brick
- Concrete
- EFIS or cement plaster
- Masonry block
- Stucco
- Porous stone
- Unglazed tile

COVERAGE RATES (THEORETICAL):

<u>All Substrates</u>	<u>Sq Ft/ Gallon</u>
Two Coats	average 100

Special Considerations:

- Use of fluted or scored block or raked joints will increase surface areas by 20%-30% or more and decrease coverage rates. Allow for this increased surface area when determining material requirements.
- Extremely porous surfaces may require multiple coats.

MANUFACTURED BY: Rainguard International 1201 Dove Street Suite 625 Newport Beach, CA 92660-2801

CONTACT INFORMATION: Phone: 949.515.8800 Fax: 949.675.3450 Email: info@rainguard.com Website: Rainguard.com

PRECAUTIONS & LIMITATIONS

All surfaces to be coated should be clean of any dirt and grime, efflorescence, lime run, form oils and release agents, grease, mud, excess mortar, and mold and mildew, etc. All cracks should be pointed or caulked. All voids, bee holes, masonry surface defects, and openings such as conduits, pipes, drains, door frames, vents, air conditioner openings, electrical openings, control joints, or any dissimilar materials should be repaired using urethane or other approved patching. May be applied to fresh concrete after 48 hours.

Dilution - Concentrate ONLY

If product is Ready To Use - DO NOT DILUTE

10/2 Year Warranty - 9 parts water, 9:1 Mix ratio

10/2 Year Warranty - 1 32 oz. Quart per 4.75 gallons of water

10/2 Warranty = 10Year Waterproof / 2 Year Graffiti

Do not apply to surfaces if moisture content is greater than 22% as measured with an electronic moisture meter. Do not apply materials in climates where freezing temperatures have existed prior to application. Allow adequate time for surfaces to thaw. Establish that air, surface, and material temperatures are above 35°F (2°C) and at least 5°F above the dew point prior to painting. Do not apply at temperatures below 35°F or when temperatures are expected to drop below 35°F within 48 hours of application. Do not apply if rain, snow, or lower temperatures are expected within 48 hours. Do not apply if relative humidity is greater than 80%.

Use material in a well-ventilated area. Protect the work of other trades. Protect shrubbery and other plants with drop cloths. Protect automobiles and all other areas not to be coated from overspray. Remove overspray from any windows, automobiles, metal, etc. as soon as possible should it occur. To prevent permanent staining, clean spills or leaks in a timely manner.

Store materials in a well-protected area between 45° and 90°F. Avoid freezing temperatures, direct sunlight, and moisture. Keep away from heat sources.

TEST PANEL

Always apply material to a mock wall or test panel. Test wall or actual surface area to determine acceptable color, surface porosity, application rates, and methods before starting general application.

FOLLOW THESE SIMPLE STEPS

1. BLOK-LOK should be applied using low-pressure airless spray equipment.
2. Avoid atomizing material by using a spray tip size of .035 to .051. Spray head should be held 8 to 12 inches from the

surface so that the flood coat runs down the wall approximately 6-12 inches below the point of application.

3. Avoid application in windy weather.
4. Trigger gun off at the end of each pass to avoid using excessive materials. Stop all applications only at corners, joints, seams, or edges.
5. Apply second coat wet on wet after first coat has been allowed to penetrate for 5 minutes. Immediately roll or brush out runs and drips to ensure even appearance.

TECHNICAL DATA

Material Type	Silane/Siloxane
Active Content	100%
Volume Solids	40%
Color of Material	Milky White
Odor	Slight Ammonia Odor
V.O.C.	<15 g/L V.O.C. Compliant
Flash Point	Non-Flammable
pH Value	Approximately 7.5
Viscosity	9.6 Seconds No. 4 Ford Cup
Weight	Approximately 8.7 lbs./gal.
Surface Dry/Recoat	Approx 1 Hour
Full Chemical Cure	5 to 7 days

TEST DATA

Wind Driven Rain	ASTM E-514-86	98.7% Leak Red
Water Pen Fed Spec	SS-W-110C	75% Min Req
		96.8% Leak Red Chloride Ion Intr
Salt Ponding NCHRP No. 244	Allowed 25%	Obtained 13.0%
Water Abs CMU ASTM C140-75	89%	Effective
Water Vapor Trans ASTM D-1653	100%	Vapor Perm
Water Repellency ASTM C67-80A	97%	Effective
Weathering ASTM G-53	2500 Hours	– No Change
Surface Burning ASTM E84	Flame Spread 0,	Smoke developed 0

LIMITED WARRANTY PROCEDURES/INFORMATION

The information contained herein is offered in good faith and is believed to be accurate. To be eligible for a Rainguard Warranty the following must occur:

1. A site visit must be conducted by an employee or agent of Rainguard and a Field Inspection Report completed.
2. A Warranty Application must be fully completed by the applicator.
3. Field Inspection Report, Warranty Application, and a copy of the distributor's invoice must be submitted to and approved by Rainguard.

This material is only warranted when applied in accordance with the manufacturer's guidelines and warranty procedures. Without adherence to these specific guidelines, no expressed or implied warranty of this product is given. Please contact Rainguard for additional information.



MANUFACTURED BY: Rainguard International 1201 Dove Street Suite 625 Newport Beach, CA 92660-2801

CONTACT INFORMATION: Phone: 949.315.8800 Fax: 949.675.3450

Email: info@rainguard.com Website: Rainguard.com