



# PRODUCT DATA SHEET

## DRYLOK® ETCH

### DESCRIPTION

DRYLOK Etch cleans and etches concrete, stone, tile and brick. DRYLOK Etch removes efflorescence (salt-like deposits) and excess mortar. It's perfect for etching concrete and galvanized surfaces prior to painting.

### SURFACE PREPARATION

Remove dirt, dust, grease and oil by washing with a detergent solution. Allow the surface to dry before applying DRYLOK Etch.

### MIXING

To remove efflorescence, clean mortar or etch galvanized surfaces, dissolve 12 ounces of Etch in one gallon of warm water; to etch concrete prior to painting, use 12 ounces of Etch to one-half gallon of warm water. Do not use galvanized container. Wear rubber gloves and eye protection.

### APPLICATION

Apply with a stiff brush. Wait 20-30 minutes. Flush thoroughly with clean water.

### TECHNICAL DATA

Contains sulfamic acid. May cause burns. Avoid contact with skin, eyes, clothing. In case of contact, flush with water for at least 15 minutes; for eyes, get medical attention. If swallowed, give 1 or 2 glasses of water. Call physician immediately. These precautions apply to both dry form and solution.

Kills plants and shrubbery. Keep out of reach of children.

For complete waterproofing protection of masonry surfaces, use DRYLOK Etch in conjunction with DRYLOK Fast Plug Hydraulic Cement and DRYLOK Masonry Waterproofer.

### AVAILABILITY

DRYLOK Fast Plug is available through local dealers and distributors. In areas not serviced, contact United Gilsonite Laboratories for details.

PRODUCT DATA  
DRYLOK ETCH

LR 1/00



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com