

# ELEPHANT SNOT®



Reg. No. ECP 02007

Graffiti Solutions

www.graffitisolutions.com

1.800.891.0091

## G R A F F I T I R E M O V E R

### GENERAL DESCRIPTION

**ELEPHANT SNOT®** Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

**ELEPHANT SNOT®** Graffiti Remover is the right choice for the job if it is a "porous surface" such as the following.

### RECOMMENDED FOR REMOVAL ON

Brick, mortar, masonry, cement, concrete, stucco, landscaping pavers, terrazzo. Natural stone surfaces such as granite, marble, sandstone, porous rocks, both rough and polished. Also effective on: glass, ceramic, porcelain, glazed tile, porous tile, grout.

### PRODUCT FEATURES AND BENEFITS

- **Non-drip** formula for easy application without messy runs and drips.
- **Fast removals** - clings to the surface for maximum penetration and maximum speed of removal.
- **Low odor** with minimum or no ventilation requirement for added safety, indoor or out.
- **Nonflammable**, noncombustible, minimal fire hazard formula.
- **All temperature** effective removals from below freezing cold (24°F) to "very hot" (90°F+) conditions.

### SAFETY INSTRUCTIONS FOR USE

- **Always wear protective eye wear and chemical resistant gloves. Can cause burns.**
- Protect all exposed skin areas with chemical resistant covering.
- If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.
- **FOR PROFESSIONAL USE ONLY.**

### GENERAL INSTRUCTIONS FOR USE

- Stir before use.
- Apply directly by brush or roller.
- Allow to penetrate affected area for 15-20 minutes (30-40 minutes cold temperatures.)
- Use power washer with 15° tip with 1000 - 3000 PSI maximum pressure. For optimum performance and speed of removal use hot water (190°F). Excellent results may be obtained with a Cold Water Power Washer with the above specifications by doubling the dwell time (30-40 minutes).
- Alternative Method: Allow to penetrate for 30-35 minutes, agitate with stiff brush, and remove with water hose at maximum nozzle pressure.
- Repeat process if necessary.
- Use **SHADOW MAX** to remove any ghosting or shadow.
- Clean up all equipment after each use with water.

### SPEC'S - GENERAL PROPERTIES

#### CONSISTENCY

No drip gel clings to vertical surfaces without dripping.

#### COVERAGE

100 to 200 Sq. ft./gal. depending on porosity of surface.

#### TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

#### STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw and remix before using. Keep out of the reach of children.

### FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

### V.O.C.S

.4 lbs/gallon, 50 grams/liter. H.A.P.S. - none.

### BIODEGRADABLE

Yes

### VOLATILITY

Very low rate of evaporation. No ventilation required unless used in a confined space.

### SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

### EFFECTIVE ON THE FOLLOWING

Paint spills on floors, spray booth over sprays, even many difficult to remove 2-part paints, epoxies, urethanes, can be removed effectively with **ELEPHANT SNOT®**.

### TEST FIRST

**ELEPHANT SNOT®** should not be used for any other purpose/removal, without thoroughly testing in an inconspicuous area for effect.

NOTE: If removing "shadows or ghosts" from any of the above surfaces we recommend the use of **SHADOW MAX** Graffiti Remover for maximum effectiveness.

For removals from all types of metals, "durable" baked on painted surfaces such as auto, bus, truck, other factory applied paints, or fiberglass, use our **SMOOTH MAX** Graffiti Remover.