

**StaticWorx TriboClean Static Dissipative  
Cleaning Solution**

**PRODUCT DESCRIPTION**

StaticWorx TriboClean is specifically designed for use in maintenance programs whose goal is to reduce static electricity buildup and increase the conductivity of surfaces in areas where sensitive electronic components are being used or manufactured. Regular cleaner and detergent compounds destroy the static-dissipating properties of highly specialized conductive floor finishes like StaticWorx Finish, rendering static-control maintenance programs ineffective. StaticWorx TriboClean removes dirt and soil while maintaining or increasing the conductivity of StaticWorx Finish, StaticWorx Buff, or StaticWorx Seal. This product is equally effective on vinyl, vinyl-asbestos, rubber, linoleum, ceramic and concrete surfaces. Environmentally safe, it is noncorrosive, nonflammable, and biodegradable.

**APPLICATION & MAINTENANCE**

Floor Surfaces should be swept or vacuumed prior to washing to remove loose dirt and soil. For use in daily or frequent damp mopping, use a diluted solution of 8 - 10 ounces of StaticWorx TriboClean per gallon of warm water. Mop the floor lightly and allow it to dry. Do not rinse. For heavier soil conditions, sweep or vacuum the floor to remove loose soil or dirt. Dilute 12 - 16 ounces of cleaner per gallon of warm water and use as a mopping solution. After cleaning, the floor may be spray buffed with StaticWorx Buff or recoated with StaticWorx Finish. Do not use plain water or regular all purpose cleaners for maintaining conductive finishes.

**SAFETY INFORMATION**

Health . . . . .	1
Flammability . . . . .	0
Reactivity . . . . .	0
Personal Protection . . . . .	B

**CAUTION:** May cause irritation in undiluted concentrations. If ingested, give vinegar, lemon or orange juice. Follow with olive oil. Do NOT induce vomiting. External contact, flood with water. In the event of eye contact, flush with plenty of clean water. Contact a physician immediately.

Contains Diethylene Glycol Methyl Ether #111-77-3. For detailed information, consult MSDS sheet.

**SPECIFICATIONS**

Active ingredients . . . . .	Anti-static and quaternary compounds
Electrostatic Decay Time . . . . .	0.1 Seconds
pH . . . . .	6.5 - 7.5
Free Ammonia . . . . .	None
Free Alkali . . . . .	None
Free Acid . . . . .	None
Phosphates . . . . .	None
Abrasives . . . . .	None
Color . . . . .	Green
Odor . . . . .	Mild Detergent
Solubility in Water . . . . .	100% Freeze/Thaw
Stability . . . . .	3 cycles
Shelf Life . . . . .	Minimum 1 year at room temperature
Flash Point . . . . .	None
Weight per Gallon . . . . .	8.3
Biodegradable . . . . .	Yes
Soil Suspension . . . . .	Good